	Stainless Steel Tubular Exchanger – 300,000 BTU	Stainless Steel Tubular Exchanger – 600,000 BTU
POWER	Delivered Power: 300,000 BTU/hr Power Output: 88 kW/hr	Delivered Power: 600,000 BTU/hr Power output: 175 kW/hr
POOL SIZE	Up to 23.80 US gal (90.10 litres or 90 m3)	Up to 47.50 US gal (179.81 litres or 180 m3)
CONNECTIONS	Side (Pool or spa water): 2 in. NPT Ends (Boiler fluid): 1 ½ in. NPT	Side (Pool or spa water): 2 ½ in. NPT Ends (Boiler fluid): 2 in. NPT
DIMENSIONS AND WEIGHT	Overall Length: 70.49 cm (27.75 in.) Overall Diameter: 12.70 cm (5 in.) Shell Diameter: 7.94 cm (3.13 in.) Weight: 4.3 kg (9.48 lb)	Overall Length: 86.36 cm (34 in.) Overall Diameter: 16.51 cm (6.5 in.) Shell Diameter: 10.80 cm (4.25 in.) Weight: 8.3 kg (18.30 lb)
TEMPERATURE	Maximum Temperature: 203°C Minimum Temperature: -10°C	Maximum Temperature: 203°C Minimum Temperature: -10°C
PRESSURE	Maximum Pressure: 6 bars	Maximum Pressure: 6 bars