

	Stainless Steel Tubular Exchanger – 300,000 BTU	Stainless Steel Tubular Exchanger – 600,000 BTU
POWER	Delivered Power: 300,000 BTU/hr Power Output: 88 kW/hr	Delivered Power: 600,000 BTU/hr Power output: 175 kW/hr
POOL SIZE	Up to 23 800 US gal (90 100 litres or 90 m3)	Up to 47 500 US gal (179 810 litres or 180 m3)
CONNECTIONS	Side (Pool or spa water): 2 in. NPT Ends (Boiler fluid): 1 ½ in. NPT	Side (Pool or spa water): 2 ½ in. NPT Ends (Boiler fluid): 2 in. NPT
DIMENSIONS AND WEIGHT	Overall Length: 70.49 cm (27.75 in.) Overall Diameter: 12.70 cm (5 in.) Shell Diameter: 7.94 cm (3.13 in.) Weight: 4.3 kg (9.48 lb)	Overall Length: 86.36 cm (34 in.) Overall Diameter: 16.51 cm (6.5 in.) Shell Diameter: 10.80 cm (4.25 in.) Weight: 8.3 kg (18.30 lb)
TEMPERATURE	Maximum Temperature: 203°C Minimum Temperature: -10°C	Maximum Temperature: 203°C Minimum Temperature: -10°C
PRESSURE	Maximum Pressure: 6 bars	Maximum Pressure: 6 bars