

	Titanium Tubular Exchanger – 300,000 BTU	Titanium Tubular Exchanger – 600,000 BTU
POWER	Delivered Power: 300,000 BTU/hr Power Output: 88 kW/hr	Delivered Power: 600,000 BTU/hr Power output: 175 kW/hr
POOL SIZE	Up to 23 800 US gal (90 100 litres or 90 m ³)	Up to 47 500 US gal (179 810 litres or 180 m ³)
CONNECTIONS	Side (Pool or spa water): 2 in. NPT Ends (Boiler fluid): 1 ½ in. NPT	Side (Pool or spa water): 2 ½ in. NPT Ends (Boiler fluid): 2 in. NPT
DIMENSIONS AND WEIGHT	Overall Length: 70.49 cm (27.75 in.) Overall Diameter: 12.70 cm (5 in.) Shell Diameter: 7.94 cm (3.13 in.) Weight: 2.28 kg (5.03 lb)	Overall Length: 86.36 cm (34 in.) Overall Diameter: 16.51 cm (6.5 in.) Shell Diameter: 10.80 cm (4.25 in.) Weight: 5.51 kg (12.15 lb)
TEMPERATURE	Maximum Temperature: 203°C Minimum Temperature: -10°C	Maximum Temperature: 203°C Minimum Temperature: -10°C
PRESSURE	Maximum Pressure: 5 bars	Maximum Pressure: 6 bars